

IN THE CLAIMS

Claim 1 (previously re-presented as Claim 21; currently canceled).

9/23 Claim 2 (currently amended). The insulating wire separator apparatus of Claim 21 24, wherein the insulating wire separator apparatus is made of a resilient, nonconductive, noncorrosive, nonbiodegradable material.

3/17 Claim 3 (currently amended). The insulating wire separator apparatus of Claim 21 24, wherein a separator post extends at right angles from said arm portion, said separator post spaced at least ten inches from said plate portion; and said arm portion extends at least two inches beyond said separator post, to provide safe spacing for additional underground utilities in a common trench location.

Claim 4 (canceled).

Claim 5 (currently amended). The insulating wire separator apparatus of Claim 21 24, wherein ~~the wire separator apparatus~~ said body is color coded, with a separate color used for each utility.

Claim 6 (currently amended). The insulating wire separator apparatus of Claim 21 24, wherein the tracer wire clip portion is located at ~~the distal~~ said other end of said arm portion.

Claim 7 (currently amended). The insulating wire separator apparatus of Claim 21 24, wherein the opening in the resilient, main conduit receiving portion is from about sixty to about eighty degrees from the centerline of the main conduit.

Claim 8 (currently amended). The insulating wire separator apparatus of Claim 21 24, wherein the tracer wire clip finger portion is angled from about three to about thirty degrees from the centerline of said arm portion; to engage varying sizes of tracer wire therein.

Claim 9 (currently amended). The insulating wire separator apparatus of Claim 21 24, wherein the main conduit receiving portion comprises an inner radius having a first half portion, with a second half portion releasably secured to said first half portion ~~with~~ by a releasable fastening means fastener.

Claim 10 (currently amended). 22: An insulating wire separator apparatus for separating a tracer wire a safe distance from a main conduit in a trench prior to back-filling, ~~which~~ comprises comprising:

Big Capital
C3
a) ~~a resilient, main conduit receiving portion having an inner radius sized to receive a main conduit portion therein, and an opening sized to flex about said main conduit~~ an elongated body having opposite ends, a resilient, main conduit receiving portion at one of said opposite ends having an inner radius size to receive said main conduit therein, an opening into said main conduit receiving portion sized to flex about said main conduit, and a pair of conduit engaging sliding wedge surfaces on opposite sides of said opening which engage said main conduit to flex said main conduit receiving portion to expand said opening and position said main conduit within said main conduit receiving portion upon the application of force between said main conduit and said conduit engaging sliding wedge surfaces of said main conduit receiving portion, said main conduit receiving portion with having an outer strengthening rib which extends about said main conduit receiving portion of the wire separator apparatus;

b) ~~an arm portion extending from the main conduit receiving portion on a side opposite said opening in the main conduit receiving portion, said arm portion extending at least six inches beyond said main conduit receiving portion~~ an arm portion extending away from said main conduit receiving portion on a side opposite said opening, said arm portion extending to the other

Claim 12 (currently amended). The insulating wire separator apparatus of Claim 22 25, wherein ~~the insulating wire separator apparatus~~ said body is color-coded with a separate color used for each utility.

Claim 13 (currently amended). The insulating wire separator apparatus of Claim 22 25, wherein the tracer wire clip portion is located at ~~the distal~~ said other end of ~~the~~ said arm portion.

Claim 14 (currently amended). The insulating wire separator apparatus of Claim 22 25, wherein the opening provided in the resilient, main conduit receiving portion is from about sixty to about eighty degrees from the centerline of the main conduit.

Claim 15 (currently amended). The insulating wire separator apparatus of Claim 22 25, wherein the tracer wire clip finger portion is angled from about three to about thirty degrees from the centerline of said arm portion; to engage varying sizes of tracer wire therein.

Claim 16 (currently amended). The insulating wire separator apparatus of Claim 22 25, wherein the main conduit receiving portion comprises an inner radius having a first half radiused portion, with a second half radiused portion releasably secured to said first half radiused portion ~~with~~ by a releasable fastener.

Claim 17 (currently amended). 23. An insulating wire separator apparatus for separating a tracer wire a safe distance from a main conduit in a trench prior to back-filling, which comprises:

a) ~~a resilient, main conduit receiving portion having an inner radius sized to receive at least one main conduit portion therein, and an opening sized from sixty degrees to eighty degrees from the centerline of the main conduit, said main conduit receiving portion with an outer strengthening rib which extends about said main conduit receiving portion of the wire separator apparatus~~ an elongated body having opposite ends, a resilient, main conduit receiving portion at

*217
Brid
Conid*

one of said opposite ends having an inner radius size to receive said main conduit therein, an opening into said main conduit receiving portion sized to flex about said main conduit, and a pair of conduit engaging sliding wedge surfaces on opposite sides of said opening which engage said main conduit to flex said main conduit receiving portion to expand said opening and position said main conduit within said main conduit receiving portion upon the application of force between said main conduit and said conduit engaging sliding wedge surfaces of said main conduit receiving portion;

b) an I-beam arm portion extending from the main conduit receiving portion on a side opposite said opening in the main conduit receiving portion, said I-beam arm portion extending at least ten inches beyond said main conduit receiving portion;

C3

c) a plate portion extending at right angles from said arm portion in proximity to said conduit receiving portion a foot plate and earth anchor portion extending generally perpendicularly from said arm portion in proximity to said conduit receiving portion whereby said force may be applied between said conduit engaging sliding wedge surfaces and said main conduit to flex said main conduit receiving portion and expand said opening to position said main conduit in said main conduit receiving portion and to resist rotation of said wire separator apparatus about said main conduit after back-filling;

d) a separator post which extends at least about two inches above said arm portion, said separator post spaced at least about ten inches along said arm portion from said plate portion;

e) a tracer wire clip portion having a pair of fingers for receiving a tracer wire therein, said fingers positioned to extend from the arm portion, midway between said separator post and the centerline of the main conduit;

f) the insulating wire separator apparatus made of a non-conductive, non-corrosive, non-biodegradable material; and

g) said arm portion extends at least about two inches beyond said separator post, to provide safe spacing for additional underground utilities in a common trench location, and to position the tracer wire a safe distance from the main conduit to protect the conduit from damage by an accidental electrical charge or ~~be~~ by a ~~lightening~~ lightning strike, said tracer wire for alerting the presence of conduit located beneath the ground after back-filling the trench.

11-
Bund
Claim 18 (currently amended). The insulating wire separator apparatus of Claim 23 24, wherein the main conduit receiving portion comprises a first half radiused portion, with a second half radiused portion releasably secured to said first half radiused portion ~~with~~ by a suitable releasable fastening means releasable fastener.

C3
Claim 19 (currently amended). The insulating wire separator apparatus of Claim 23 26, wherein the tracer wire clip finger portion is angled from about three to about thirty degrees from the centerline of said arm portion; to engage varying sizes of tracer wire therein.

Claim 20 (currently amended). The insulating wire separator apparatus of Claim 23 26, wherein ~~the insulating wire separator apparatus~~ said body is color-coded, with a separate color used for each utility.

Claim 21 (canceled).

Claim 22 (canceled).

Claim 23 (canceled).

sub C3
Claim 24 (new). An insulating wire separator apparatus for separating a tracer wire a safe electrically insulative distance from a main conduit in a trench prior to back-filling comprising:

a) an elongated body having opposite ends, a resilient, main conduit receiving portion at one of said opposite ends having an inner radius size to receive said main conduit therein, an opening into said main conduit receiving portion sized to flex about said main conduit, and a pair of conduit engaging sliding wedge surfaces on opposite sides of said opening which engage said main conduit to flex said main conduit receiving portion to expand said opening and position said main conduit within said main conduit receiving portion upon the application of force between said main conduit and said conduit engaging sliding wedge surfaces of said main conduit receiving portion;

b) an arm portion extending away from said main conduit receiving portion on a side opposite said opening, said arm portion extending to the other of said opposite ends, an electrically insulative safe distance beyond said main conduit receiving portion;

c) a foot plate and earth anchor portion extending generally perpendicularly from said arm portion in proximity to said conduit receiving portion whereby said force may be applied between said conduit engaging sliding wedge surfaces and said main conduit to flex said main conduit receiving portion and expand said opening to position said main conduit in said main conduit receiving portion and to resist rotation of said wire separator apparatus about said main conduit after back-filling; and

d) a tracer wire clip portion for receiving a tracer wire therein, said tracer wire clip portion being positioned on said arm portion adjacent to said other end to position the tracer wire said safe distance from said main conduit from said main conduit receiving portion and said conduit therein to protect said conduit from being damaged.

Claim 25 (new). The insulating wire apparatus of Claim 24 wherein said main conduit receiving portion has a outwardly extending strengthening rib which extends between said conduit engaging sliding wedge surfaces and said arm portion.

Claim 26 (new). The insulating wire apparatus of Claim 24 wherein said tracer wire clip portion has a pair of fingers for receiving a tracer wire therebetween.

Claim 27 (new). The insulating wire apparatus of Claim 24 further comprising a separator post extending generally perpendicularly from said arm portion in proximity to said tracer wire clip portion.

Claim 28 (new). The insulating wire separator apparatus of Claim 24, wherein the opening provided in the resilient, main conduit receiving portion is from about sixty to about eighty degrees from the centerline of the main conduit.

Claim 29 (new). The insulating wire separator apparatus of Claim 24, wherein the tracer wire clip portion is angled from about three to about thirty degrees from the centerline of said arm portion to engage varying sizes of tracer wire.